

Product image (Omni_IRO-02(2G))



Physical Characteristics

Dimensions(mm)	122×12
Weight(g)	≤30
Connector Type	SMA-Male
Input Power	≤1W

Electrical Characteristics

Frequency Range	2500 MHz ~ 2700 MHz
Polarization	Vertical
Nominal Impedance	50Ω
Gain	<2 dBi
V.S.W.R	≤2.0:1
3dB Beamwidth	Horizontal: Omni Vertical: ∞

Product image (Omni_IRO-02(3G))



Physical Characteristics

Dimensions(mm)	122×12
Weight(g)	≤30
Connector Type	SMA-Male
Input Power	≤1W

Electrical Characteristics

Frequency Range	3300 MHz ~ 3800 MHz
Polarization	Vertical
Nominal Impedance	50Ω
Gain	<2 dBi
V.S.W.R	≤2.0:1
3dB Beamwidth	Horizontal: Omni Vertical: ∞

Product image (Omni_IRO-06(2G))



Physical Characteristics

Dimensions(mm)	210×12
Weight(g)	≤40
Connector Type	SMA-Male
Input Power	≤1W

Electrical Characteristics

Frequency Range	2300 MHz ~ 2700 MHz
Polarization	Vertical
Nominal Impedance	50Ω
Gain	6 dBi ±0.5
V.S.W.R	≤2.0:1
3dB Beamwidth	Horizontal: Omni Vertical: ∞

Product image (Omni_IRO-06(3G))



Physical Characteristics

Dimensions(mm)	210×12
Weight(g)	≤40
Connector Type	SMA-Male
Input Power	≤1W

Electrical Characteristics

Frequency Range	3400 MHz ~ 3800 MHz
Polarization	Vertical
Nominal Impedance	50Ω
Gain	≥5.5 dBi
V.S.W.R	≤2.0:1
3dB Beamwidth	Horizontal: Omni Vertical: ∞